



## IEB-54F0036M0A

Article number: 217365

1/3" Network Camera, Day&Night, 2592x1520, H.265, Infrared, 3.6mm, PoE, IP66

### Mainfeatures

1/3" Omnivision CMOS sensor

Resolution max. 2592x1520

Cross-Web-Browsing

Tampering, Defog

Framerate increase on motion detection

Fixed 3.6mm, Day&Night lens

Compression H.265/ H.264/ MJPEG

ROI Hi-Stream to reduce the bandwidth

D-WDR (Digital Wide Dynamic Range)

Compact design, Outdoor applications, IP66

### Specifications

Camera:	
Sensor size	1/3"
Imager	CMOS, OmniVision (4689)
System	True Day&Night
Sensitivity	0,1 Lux, 50 IRE
Low speed shutter	yes
Manual electronic shutter (MES)	1~1/30.000sec.
Automatic electronic shutter (ESC)	1~1/30.000sec.
Wide Dynamic Range (WDR)	D-WDR
Backlight compensation	no
IR cut filter	switchable
White balance	automatic, manual
Signal-to-noise ratio	50dB
Video:	

# IEB-54F0036M0A

## Continued Specifications

Resolution	2 Megapixel Modus @ 30fps, 4 Megapixel Mode @20fps, 2592x1520 (16:9), 2048x1536 (4:3), 1920x1080 (16:9), 1280x1024 (5:4), 1280x960 (4:3), 1280x720 (16:9), 1024x768 (4:3), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 640x360 (16:9), 320x240 (4:3)
Stream types	1x H.265, 1x H.264, 1x MJPEG multiple
Image transmission rate max.	30 fps
Multicast compliant	yes
Compression standard	H.264, M-JPEG
<b>Lens:</b>	
Lens type	fixed focal length
Focal length	3,6 mm
MOD (Minimum object distance)	0,3 m
Iris control	DC
Vertical angle of view	45 °
Horizontal angle of view	83 °
<b>Features:</b>	
Motion detector	yes
Analysis functions	tampering protection
Alarm processing	E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML
Audio support	no
Password protection	included
Internal storage	no
Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
Privacy zones masking	Areas-ON/OFF switchable
Remote configuration	web browser
Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG
User interface	Type B (white / blue)
Mirror function	H-flip, mirror
Digital Noise Reduction (DNR)	yes, 17
<b>Network:</b>	
Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS
<b>Interfaces / Inputs / Outputs:</b>	
External connections	RJ-45, 12VDC input (DC plug)
Ethernet interface	10Base-T, 100Base-TX
Alarm inputs	no
Alarm outputs	no
<b>General:</b>	
Series	eneo Economy Class
Dimensions (HxWxD)	76,6x75,8x150,4mm
Illumination	infrared, 1x High Power LED 850nm
Illumination range	approx. 30m
Colour (housing)	white

# IEB-54F0036M0A





## Continued Specifications

Housing	outdoor
Housing material	aluminium
Weight	300g
Integrated wall mount	yes
Power consumption	5,1W
Blower	no
Mounting	wall mount, ceiling mount
ONVIF	ONVIF Profile S
Power over Ethernet	IEEE 802.3af
Window heater	no
Protection rating	IP66
SDK	upon request
Hidden cable management	yes
Sunshield	no
Supply voltage	PoE, 12VDC
Temperature range (operation)	-20°C ~ +50°C
Text display	supplied
<b>Scope of delivery:</b>	
Parts supplied	manual, mounting accessories, eneo Site Manager
<b>Notes:</b>	

# IEB-54F0036M0A

## Available Accessories

Image	Prod. No / Label	Description
	70543 / VT-PS12DC-10	Plugable AC/DC Adapter 100-240V/12VDC- 2.5A, stab., Cont. & UK Mains plug-ins
	210144 / eneo Scan Device	Management program for eneo IP Cameras
	211980 / EVX-900R	Media Converter, Indoor, Transmitter-Receiver, 1x RJ45, 1x RJ-11, 12V, up to 1000m
	211981 / EVX-900B	Media Converter, indoor, Transmitter-Receiver, 1x RJ45, 1x BNC, 12V, up to 1000m
	211982 / EPS-1008	PoE Switch, 8x PoE+, 1x RJ45, 1x SFP, 130W, Metal Housing
	214460 / IAR-7SE1024MMA	Gigabit Switch, 2x RJ45, 24x PoE 100Mbps, 2xSFP 1000Mbps, 390W, Managed, 19", 1U
	214459 / IAM-5SE1008MUA	Gigabit Switch, 8xPoE 100Mbps, 1x RJ45, and 1x SFP 1000Mbps, Unmanaged, Industrial Design
	214731 / IAM-5SE1004MUA	Gigabit Switch, 4x PoE, 2x RJ45 and 2x SFP 1000Mbps, Unmanaged, Industrial Design
	216129 / IAM-5SG1008MMA	Gigabit Switch, Managed, 240W, 8x PoE, 4x SFP, 1000Mbps, Industrial Design, -40°C~+75°C
	216469 / IAD-5SG1004MUA	Gigabit Switch, Unmanaged, 60W, 4x PoE, 2x RJ45, 10/100/1000 Mbps, Desktop
	216472 / IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

<p>www. y.com</p> 	<p>216473 / IAR-7SG1008MMA</p>	<p>Gigabit Switch, Managed, 135W, 8x PoE, 2x SFP, 2xRJ45, 10/100/1000 Mbps, 19", 1 U</p>
	<p>216474 / IAR-7SG1016MMA</p>	<p>Gigabit Switch, Managed, 270W, 16x PoE, 4x SFP, 10/100/1000 Mbps, 19", 1HU</p>
	<p>216682 / IAR-7SG1024MMA</p>	<p>Gigabit Switch, Managed, 390W, 24x PoE, 4x SFP, 10/100/1000 Mbps, 19", 1HU</p>
	<p>218218 / eneo Site Manager</p>	<p>Management Software for eneo IP Cameras</p>

## Your Contact Person

	<p>TechWare Finland Oy          Koivupuistontie 26          01510 Vantaa          FI          Tel.: +358 (0)20 720 9650          E-Mail: info@techware.fi          Web: www.techware.fi</p>
---	---